

Security Panic Hardware

ASSURE panic hardware

Panic locks and latches - Push Bar



Application

Light-action push plates which operate mortice escape sash locks or nightlatches. ASSURE offers very high security. Suitable for public areas and places where a panic situation could arise.

Cylinders



- ASSA 5-Pin
- ASSA Flexcore Plus
- ASSA 4800
- ASSA Twin Combi
- ASSA dp4400
- ASSA CLIQ

Scandinavian Oval or Round

Can be incorporated into an ASSA master key system



Panic latch operator, supplied with lockcase, strike and external blind rose. Cylinder and other door furniture supplied separately.


Clearly labelled at point of use.

Available in satin anodised aluminium finish.

Latch handing is reversible, but when specifying the 1520 version the handing and direction of door opening should be specified.

Microswitching available as an option.

ASSURE 1520 Bar



Panic lock with deadbolt, for single doors.


Escape from inside is possible at all times, even when the deadbolt has been thrown. Door is secured by a steel deadlocking latchbolt, with the option of using a key externally to throw a 25mm hardened steel deadbolt for additional night-time security. Suitable for door widths 925 - 1300 mm.



Product has been successfully type-tested for conformity to EN 1125. Regular audit testing is undertaken.

Please note that when specifying split follower locks it is important to state the direction of door opening as well as the handing.


ASSURE 8761 Bar



Panic latch, for single and double doors.

Escape from inside is possible at all times. Door is secured by a steel deadlocking latchbolt. Suitable for door widths 925 - 1300 mm.

ASSURE 8761D Bar - variant with packing pieces behind push bar, for use with ASSURE 200 two-point panic bolt on double doors. Also requires use of Modular rebate kit and 10 22 84 striking plate, supplied separately.



Product has been successfully type-tested for conformity to EN 1125. Regular audit testing is undertaken.

Also available with the 8762 or 8759 lockcase in place of the 8761. See Lockcases section for details.

Refs: 8762 Bar, 8759 Bar, 8762D Bar, 8759D Bar.