

Model 76-57R-88035Q31



Electric Strike 76-57R-88035Q31

Most user friendly and versatile strike in the market. Designed for medium-duty applications, this all-in one electric strike offers dual voltage and field selectable fail secure/fail safe operation. The latch cavity accommodates cylindrical locksets with a 1/2" to 5/8" throw (5/8" requires 1/8" door gap) in wood or aluminum frames. Monitoring included as standard and Built-in electronic (Buzzer).

Overview of Advantages

- 12/24 V AC/DC
- Fail safe/ fail secure
- Monitored
- Pre load (Fail secure only)
- Grade 2
- Stainless steel 7-15/16" x 1-7/16" plate
- easy to install and connect
- universal handing
- 5 year limited warranty

Scope of delivery

- 1 electric strike
- 1 LIP bracket
- 1 Stainless steel 7-15/16" x 1-7/16" plate

Characteristics		Technical data	
Adjustable latch (FF, FaFix®)	•	Voltage	12/24 V AC/DC
Fail-Safe	•	Break-in resistance	1,500 lbs
Fail-Secure	•	Operating temperature range	-10 °C to +40 °C
		Installation position	vertical and horizontal
		Load cycles for in-plant test	500,000
		Suitability for fire protection	No
		Inrush current 0.5 sec. Max.	500 mA
		Rated current consumption 12 V DC	130 mA
		Rated current consumption 24 V DC	70 mA
		Rated current consumption 12 V AC	200 mA
		Rated current consumption 24 V AC	70 mA
		Max. latch preload AC	>20 lbs
		Max. latch preload DC (stabilised)	>20 lbs

DIN direction	
universal	1

Voltage	
12/24 V AC/DC	Q3

Order no.	
76-57R-88035	** *