

Electric strike

76-57R-87735Q31



Most user friendly and versatile strike in the market.

Designed for medium-duty applications, this all-in one electric strike offers dual voltage and field selectable fail secure/fail safe operation.

The latch cavity accommodates cylindrical locksets with a 1/2" to 5/8" throw (5/8" requires 1/8" door gap) in wood or aluminum frames.

Monitoring included as standard and Built-in electronic (Buzzer).

Overview of Advantages

- 12/24 V AC/DC
- Fail safe / fail secure
- Monitored
- Pre load (Fail secure only)
- Grade 2
- Stainless steel 4-7/8" x 1-1/4" plate
- easy to install and connect
- universal handing
- 5 years limited warranty

Scope of delivery

- 1 piece electric strike
- 1 piece LIP bracket
- 1 piece stainless steel 4-7/8" x 1-1/4" plate

Technical data	
Voltage	12/24 V AC/DC eE
Adjustable latch (FF, FaFix®)	Yes
Fail-locked	Yes
Fail-unlocked	Yes
Break-in resistance	1,500 lbs
Operating temperature range	-10 to +40
Installation position	vertical and horizontal
Load cycles for in-plant test	500000
Fire protection	No
Inrush current 0,5 sec. Max.	500 mA
Rated current consumption 12 V DC	130 mA
Rated current consumption 24 V DC	70 mA
Rated current consumption 12 V AC	200 mA
Rated current consumption 24 V AC	70 mA
Max. latch preload AC 12-24V	20 lbs
Max. latch preload DC 12V	40 lbs
Max. latch preload 24V	65 lbs
Article number	
76-57R-87735Q31	